

A New Pow[®]

Made In Taiwan

Green

Efficient

Quiet

**E-Partner[®] Series
Multi-Purpose Mobile AC Power**



Flexible



E-Partner[®] 15 / E-Partner[®] 22 LiFePO₄ Battery Energy

Cleaner Than Generator

- ◆ AP4815 LiFePO₄ (700WH)
- ◆ AP4822 NMH (1000WH)
- ◆ LED Display Gauge
- ◆ Capacity Status Window
- ◆ Battery (Replaceable)

Safe



Capacity Status Window

Expandable

Intelligent



Money Saving

Fire and Rescue

Electric Tools



EMT Services



Mobile Cafes



Robust and Versatile

Quiet

- ◆ 6" Rubber Wheels, Wading Depth (10cm)
- ◆ Intelligent Leakage Detection
- ◆ Capacity Status Window
- ◆ IP44 Waterproof
- ◆ Waterproof Socket Cover
- ◆ Power Cord Storage Tray

Inverter :

- ◆ 110V Pure Sinewave Output
- 2000W Supporting Electric Power Drill (Battery and Inverter).
- 1200W Supporting Medical, Camping and Small Electric Devices (Battery and Inverter)



Convenient

Waterproof

Flexible



Waterproof Socket Cover



Power Cord Storage Tray



6" Rubber Wheels



1200W



2000W



Street Performance



Outdoor Power



Medical Devices



Off-Grid Camping

Battery Spec.

Item	AP4815	AP4822
Battery Type	LiFePO ₄	Li-NMC
Capacity	700WH	1000WH
Max. Charge Voltage	58.4V	58.8V
Rated Voltage	51.2V	51.8V
Cycle Life (Remaining Capacity 80%)	1000	500
Weight	9±0.5Kg	8±0.5Kg
Dimensions (L*W*H)	248*183*200mm	

E-Partner® 15 / E-Partner® 22 Common Spec.

Item	Spec.
Operating Temp.	-20~60°C
Operating Humidity	~85%RH
Weight	25Kg±5%
Dimensions (L*W*H)	270*330*1080mm

E-Partner® 15 Spec. (AP4815 LiFePO₄)

Item	AN07111K	AN07221K	AN07112K	AN07222K
Output Voltage Socket *2	110V	220V	110V	220V
Continuous Output Power	1200W	1200W	2000W	2000W
AC Input Voltage	88~132V	176~264V	88~132V	176~264V

E-Partner® 22 Sepc. (AP4822 Li-NMC)

Item	AN08111K	AN08221K	AN08112K	AN08222K
Output Voltage Socket*2	110V	220V	110V	220V
Continuous Output Power	1200W	1200W	2000W	2000W
AC Input Voltage	88~132V	176~264V	88~132V	176~264V

Optional :

PV IN Optional (DC25V~50V)

Solar Panel Spec.

Configuration	Q'ty	Dimension	Weight	Voltage	Power
Single	1	1019*992*40mm	12Kg	22.51V	150W
Standard	2	1019*992*40mm*2	24Kg	45.02V	300W

Lightweight Solar Panle Spec.

Configuration	Q'ty	Dimension	Weight	Voltage	Power
Single	1	1000*400mm	1Kg	6V	50W
Standard	6	1000*400mm*6	6Kg	36V	300W



ANEWPOW possesses the right to modify and or change the specifications without prior notice.

ANewPOW®

新銳動能有限公司

13F., No.29-2, Sec. 2, Zhongzheng E. Rd.,
251 Tamsui Dist., New Taipei City, Taiwan
TEL: 886 2 2809 1616
FAX: 886 2 2809 3363
www.anewpow.com
info@anewpow.com

Distributors